

OMNIDRIVE

General Purpose

OEM Replacement Motors



- Shaded Pole & P.S.C. Design
- Self Aligning Sleeve & Ball Bearings
- Thermally Protected
- Open & TEAO Construction
- (*) Indicates Motors are P.S.C Design & (●) Indicates Motors are Ball Bearing

Stock #	Diameter	HP	Volts	Amps.	RPM	"C"	Shaft	CFM	Replaces
UB1	Blower	1/30	115	1.10	2860	6.00"	----	140	RB1, B24220
UB3	Blower	1/50	120	0.80	3000	5.42"	----	100	RB3, B30
UB160	Blower	1/33	115	1.10	1550	5.00"	----	160	RB160, 50755-D500
UB265	Blower	1/25	115	1.40	1500	7.00"	----	265	RB265, B45227
UB465	Blower	1/15	115	2.60	1550	10-1/2"	----	465	RB465, B45267
SS208	3.3"	1/40	115	1.20	1550	2.50"	5/16" x 1.95"	CCWSE	R208
SS409	3.3"	1/50	115	1.30	1550	2.12"	5/16" x 1.56"	CWSE	R409, D126
SS356	3.3"	1/20	115	1.80	1550	2.59"	5/16" x 2.30"	CWSE	R356, D132
SS357	3.3"	1/20	115	1.80	1550	2.59"	5/16" x 2.30"	CCWSE	R357, D133
UFM78 ●*	3.3"	1/10	115 / 230	1.30 / 0.70	3200	4-1/8"	5/16" x 3.25"	REV.	RFM78
UFM653 ●	3.3"	1/12	230 / 460	1.20 / 0.60	3000	6-3/4"	1/4" x 2.25"	CCWSE	RFM653
UFM3714 ●*	3.3"	1/8	115 / 230	1.60 / 0.80	3200	7-1/8"	1/4" x 4.00"	REV.	RFM3714
SS958	4.1"	1/8	115	3.80	1550	3.94"	3/8" x 2.44"	CWSE	R2390
SS2398	5.0"	1/8	115	5.00	1050	3.87"	1/2" x 3.75"	CWSE	R2398
SS2930	5.0"	1/10	115 / 230	4.10 / 2.00	1050	3.87"	3/8" x 2.80"	CWSE	R2940
SS2932	5.0"	1/10	115 / 208-230	5.00 / 2.50	1550	3.87"	3/8" x 2.80"	CCWSE	R2932
SS2940	5.0"	1/10	115 / 230	4.10 / 2.00	1050	3.87"	3/8" x 2.80"	CCWSE	R2940
SS2942	5.0"	1/10	115 / 208-230	5.00 / 2.50	1550	3.87"	3/8" x 2.80"	CWSE	R2942

