

# OMNIDRIVE

## 3.3" Diameter Hubless Fan Design

Commercial Refrigeration, Condensers, Unit Coolers & Display Cases



SS124 - SS125



SS101 - SS103 - SS122 - SS137



SS101L - SS103L



SS119 - SS120 - SS133




SS250



SS108 - SS123



SS127



- Totally Enclosed Construction
- Threaded Shaft (5/16") with Speed Nut
- Continuous Duty
- Class 'B' insulation
- UL Listed & CSA Approved
- Shaded Pole
- Thermally Protected
- 60 Hz
- Sleeve & Ball Bearings
- (●) Indicates motors are ball bearing

| Stock # | HP    | Volts | Amps. | RPM  | "A"   | Rotation | Comments  | Replaces                        |
|---------|-------|-------|-------|------|-------|----------|---|---------------------------------|
| SS124 ● | 1/20  | 115   | 1.55  | 1550 | 2.80" | CWSE     | Lyall Cord & Plug / 4 Bolt Mounting                         | Foster / Dunham Bush / Hussmann |
| SS133   | 1/30  | 115   | 1.10  | 1550 | 2.59" | CWSE     | 2 Speed   | Markhot                         |
| SS101   | 1/45  | 115   | 0.90  | 1550 | 2.40" | CCWSE    | Lyall Cord & Plug / 2 or 3 Bolt Mounting                    | Foster / Hussmann               |
| SS101L  | 1/45  | 115   | 0.90  | 1550 | 2.34" | CCWSE    | Lyall Cord & Plug / "L" Mounting Bracket                    | Foster / Hussmann               |
| SS103   | 1/45  | 115   | 0.90  | 1550 | 2.34" | CWSE     | Lyall Cord & Plug / 2 or 3 Bolt Mounting                    | Foster / Hussmann               |
| SS103L  | 1/45  | 115   | 0.90  | 1550 | 2.34" | CWSE     | Lyall Cord & Plug / "L" Mounting Bracket                    | Foster / Hussmann               |
| SS137   | 1/70  | 115   | 0.59  | 1550 | 2.19" | CCWSE    | 3 Prong Lyall Cord & Plug / 2 or 3 Bolt Mounting            | Coldstream                      |
| SS119   | 1/70  | 115   | 0.70  | 1550 | 2.25" | CWSE     | 2 or 3 Bolt Mounting  | Foster                          |
| SS120   | 1/70  | 115   | 0.62  | 1550 | 2.25" | CCWSE    | 2 or 3 Bolt Mounting  | Foster                          |
| SS123   | 1/70  | 115   | 0.60  | 1550 | 2.59" | CCWSE    | Double "U" Bracket  | Ideal                           |
| SS250   | 1/70  | 115   | 0.65  | 1550 | 3.71" | CWSE     | 3 Bolt Mounting Shaft End / 2 Speed Switch with Cord & Plug | Wood Stove                      |
| SS127   | 1/75  | 120   | 0.78  | 1600 | 2.00" | CWSE     | 2 Bolt Mounting Shaft End / Hex Hub Shaft End               | Foster                          |
| SS108   | 1/100 | 115   | 0.60  | 1550 | 2.00" | CWSE     | "U" Bracket   | Hunter / Ideal / Lear           |
| SS125 ● | 1/20  | 230   | 0.80  | 1550 | 2.80" | CWSE     | Lyall Cord & Plug / 4 Bolt Mounting                         | Foster / Hunter / Dunham Bush   |
| SS122   | 1/60  | 230   | 0.35  | 1550 | 2.47" | CCWSE    | Lyall Cord & Plug / 2 or 3 Bolt Mounting                    | Coldstream / Foster             |

