


OMNIDRIVE

3.3" Diameter Draft Inducer Motors



UFM3714



UFM410



UFM78



131410



UFM653



148053



148055

- Continuous Duty
- Class 'B' Insulation
- UL Listed & CSA Approved
- (*) Indicates Motors are P.S.C Design
- Thermally Protected
- Sleeve & Ball Bearings
- 60 Hz.
- (●) Indicates Motors are Ball Bearing

Stock #	HP	Volts	Amps.	RPM	"A"	Shaft	Rotation	Comments	Replaces
UFM3714 **	1/8	115/230	1.6 / 0.8	3200	6.98"	1/4" x 4.00"	REV.	Conduit Box 1/4" to 5/16" Bushing	Carrier / Gen. Replacement
UFM410 **	1/10	115/230	1.4 / 0.7	3000	6.98"	1/4" x 3.70"	REV.	Conduit Box - 3 Mounting Lugs Stainless Shaft 1/4" to 5/16" Bushing	Reznor / Fasco
UFM78 **	1/10	115/230	1.3 / 0.7	3200	4-1/8"	5/16" x 3.25"	REV.	4 Mounting Studs on each end - No Switch	Reznor / 43846 & 43424
131410 **	1/10	115	1.60	3000	4.10"	5/16" x 3.20"	CWLE	No Conduit Box	Reznor / 131410
UFM653 *	1/12	230/460	0.60	3200	6-3/4"	1/4" x 2.25"	CCWSE	Conduit Box - 1/4" to 5/16" Bushing	Carrier / York
148053 **	1/20	115	0.70	3300	4.54"	5/16" x 3.00"	CWSE	4 Mounting Studs	Reznor / 148053
148055	1/33	115	1.00	3300	3.26"	5/16" x 2.00"	CWSE	Sleeve Bearing	Reznor / 148055

