


OMNIDRIVE

56C Frame Three Phase Motors Rolled Steel TEFC



All Models



- Rolled Steel Construction
- Ball Bearings
- Continuous Duty
- Class 'B' Insulation
- UL Listed & CSA Approved
- 40°C Ambient
- Rigid Base
- Removable Bolt-on Base

Stock #	HP	Volts	Amps.	RPM	"C"	S.F.
WE681C	1/3	208-230 / 460	1.62 / 0.82	1770	12.60"	1.15
WE661C	1/3	575	0.65	1800	12.60"	1.15
WE612C	1/2	575	0.82	3600	12.60"	1.15
WE682C	1/2	208-230 / 460	2.20 / 1.10	1800	12.60"	1.15
WE662C	1/2	575	0.88	1800	12.60"	1.15
WE613C	3/4	575	0.90	3600	12.60"	1.15
WE683C	3/4	208-230 / 460	2.80 / 1.40	1800	12.60"	1.15
WE663C	3/4	575	1.00	1800	12.60"	1.15
WE614C	1	575	1.30	3600	12.60"	1.15
WE684C	1	208-230 / 460	3.40 / 1.70	1800	12.60"	1.15
WE664C	1	575	1.40	1800	12.60"	1.15
WE615C	1.5	575	1.80	3600	12.60"	1.15
WE685C	1.5	208-230 / 460	4.60 / 2.30	1800	12.60"	1.15
WE665C	1.5	575	1.82	1800	12.60"	1.15
WE616C	2	575	2.10	3600	12.60"	1.15
WE686C	2	208-230 / 460	5.80 / 2.90	1800	12.60"	1.15
WE666C	2	575	2.40	1800	12.60"	1.15
WE617C	3	575	3.10	3600	13.00"	1.15

